

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-063312

(43)Date of publication of application : 13. 03. 2001

(51)Int. CI.

B60C 9/22

B60C 9/00

D02G 3/48

(21)Application number : 11-238546

(71)Applicant : BRIDGESTONE CORP

(22)Date of filing : 25. 08. 1999

(72)Inventor : OSHIMA KAZUO
NAKAMURA MASAOKI

(54) RADIAL TIRE

(57)Abstract:

PROBLEM TO BE SOLVED: To enhance high-speed durability and noise reduction.

SOLUTION: In this radial tire, a belt reinforcing layer is arranged so as to cover a whole and both ends of a belt layer, a cord reinforcing the belt reinforcing layer comprises a polyester and is endlessly and helically wound so as to be substantially parallel in a tire peripheral direction. Even in an adhesion test between the cord and a rubber at a temperature of 180°C, the rubber is adhered to the cord, and adhesion between the cord and the rubber at 180°C is not less than 80% of the adhesion at an ordinary temperature.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision
of rejection][Kind of final disposal of application
other than the examiner's decision of
rejection or application converted
registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's
decision of rejection][Date of requesting appeal against
examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998, 2003 Japan Patent Office